

Filter options for JRC NRD-5XX series

CRYSTAL FILTERS

Produced by NDK, Nihon Dempa Kogyo Co. Ltd

| Option | NDK # | -6dB Width |
|----------|----------|------------|
| CFL-231 | YF455FM | 240 Hz |
| CFL-230 | YF455DBP | 300 Hz |
| CFL-232 | YF455DQ | 500 Hz |
| CFL-233 | YF455DE | 1.0 kHz |
| CFL-218A | YF455EBF | 1.8 kHz |
| CFL-251 | YF455EB | 2.4 kHz |

| | |
|---------|--|
| CFL-316 | 0.5 KHz (9 MHz IF) |
| CFL-317 | 1.8 kHz (9 MHz IF) |
| CFL-318 | 2.7 kHz (9 MHz IF) (Standard on JST-245) |

These JRC filters are DC coupled. Need 0.01 uF in series to fit with other (ICOM) receivers.

Murata 455 kHz filters

| | |
|-----------|---------|
| CFJ455K13 | 2.6 kHz |
| CFK455J | 3.6 kHz |
| CFW455IT | 5.1 kHz |
| CFU455G | 9.5 kHz |

MECHANICAL FILTERS

Produced by Kokusai Electric Co. Ltd, Tokyo

| Option | Kokusai # | -6dB Width |
|---------|---------------|--|
| CFL-260 | MF455-03AZ | 600 Hz |
| | MF455-10AZ121 | 2400 Hz (Standard 2,4 kHz filter in NRD-515) |



Optional filter board for NRD 515 with 2,4 kHz mechanical Filter and a NDK crystal filter (same size as YF-series)

Filter options for ICOM



NDK crystal filters for NRD-5XX receivers